



FX 2 Code Table



FIXTURE

Model	Grade*	LED	Colour (CCT)		Length Availability**		IP	Cable Length		Power Feed***		Input				
FX	s	902	1900K ¹	19K	FX IP20	m	125-7000mm 62.5mm increments	IP20	20	50mm (1.97in)	a	Single tail	1	DC 24V	g	
			2100K	21K												
			2300K	23K												
						FX IP65	m	127-7002mm 62.5mm increments	IP65	65	300mm (11.81in)	c	Double tail	2		
	2500K		25K													
	2700K		27K													
						FX IP20	i	4.92-275.59in 2.46in increments					Single IP20 connector ²	3		
	3000K		30K													
	3200K ¹		32K													
						FX IP65	i	5.00-275.67in 2.46in increments					Double IP20 connector ²	4		
	3500K		35K													
	4000K		40K													
								(Specify length code OR total run length)								
					RED	RED										
					GREEN	GRN										
			BLUE	BLU												
			ORANGE	ORN												
			AMBER	AMB												

¹ 1900K is only available in k-line, 3200K is only available in s/e-line

² Not available for IP65

* Refer to **LED Grading Key** on **Specification sheet** page

** Refer to **Length Availability List** or enter total run length instead of length code

Code Example:

FX	-	s	-	902	-	35K	-	m	-	502	-	20	-	a	-	4	-	g
FX		s		FX90		3500K		502mm		IP20		50mm (1.97in)		Double IP20 connector		DC 24V		

ACCESSORIES

Mounting Accessories

KKCP-07	Side clip
KKCP-08	IP65 Side clip
KKBK-14	IP65 Silicone bracket

* Refer to **Mounting Accessories** on **Accessories** pages

Connection Accessories

KKCN-01	2 PIN male & female 50mm (1.97in) pair
KKCN-03	2 PIN male & female 300mm (11.81in) pair
KKCN-06	2 PIN 300mm (11.81in) extension lead

* Refer to **Connectors** on **Accessories** pages

PSU/Driver

0-10V/1-10V/Dali/DMX

* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

LED ENGINE VARIANTS (LED STRIP TYPE)

Luminaire	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
FX	902	560	171	7	2.13	FX	125-7000mm (4.92-275.59in) (IP20) 127-7002mm (5.00-275.67in) (IP65)	62.5mm (2.46in)
FX RGB	901	Red 733 Green 183 Blue 28 White 267	Red 223 Green 56 Blue 9 White 81	9.8	2.99	FX RGB	125-7000mm (4.92-275.59in) (IP20) 127-7002mm (5.00-275.67in) (IP65)	125mm (4.92in)

* Performance data: s/e-line, 3000K