

Groove IN (HCRI) Code Table



FIXTURE

Model	Finish	Cover	Grade*	LED	Colour (CCT)	Length Availability**	IP	Cable Length	Power Feed***	Input											
Groove IN	GN	Silver Anodised	SA	Diffused	C	s	s	103	2700K	27K	m	115-1015mm 100mm increments	IP40	40	300mm (11.81in)	c	Single tail	1	DC 24V	g	
									3000K	30K				IP65			65	Double tail			2
									4000K	40K				i			4.53-39.96in 3.94in increments				
											(Specify length code OR total run length)										

* Refer to **LED Grading Key** on **Specification sheet** page

** Refer to **Length Availability List** or enter total run length instead of length code

Code Example:

GN	-	SA	-	C	-	s	-	103	-	30K	-	m	500	-	40	-	c	-	2	-	g
Groove IN		Silver Anodised		Diffused		s		103		3000K		m	515mm		IP40		300mm (11.81in)		Double tail		DC 24V

ACCESSORIES

Connection Accessories

KKCN-01	2 PIN male & female 50mm (1.97in) pair
KKCN-03	2 PIN male & female 300mm (11.81in) pair
KKCN-06	2 PIN 300mm (11.81in) extension lead

PSU/Driver

0-10V/1-10V/Dali/DMX

* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

* Refer to **Connectors** on **Accessories** pages

LED ENGINE VARIANTS (LED STRIP TYPE)

Luminaire	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Groove IN (HCRI)	103	32	10	7.7	2.34	Groove IN HCRI	115-1015mm (4.53-39.96in)	100mm (3.94in)
Groove IN RGB	101	Red 2 Green 10 Blue 3 White 15	Red 0.6 Green 3 Blue 1 White 5	21.6	6.58	Groove IN RGB	115-1015mm (4.53-39.96in)	100mm (3.94in)

* Performance data: 3000K