



KKFS Code Table



FIXTURE

Model	Grade*	LED	Colour (CCT)	Length Availability**	IP	Cable Length	Power Feed***	Input															
KKFS	FS	s	113	2700K 27K	KKFS IP20	m	125-7000mm 62.5mm increments	IP20	20	50mm/1.97"	a	Single tail	1	DC 24V	g								
												3000K 30K	KKFS IP65			m	127-7002mm 62.5mm increments	IP65 ¹	65	300mm/11.81"	c	Double tail	2
												4000K 40K										Single IP20 connector ²	3
												Double IP20 connector ²										4	
KKFS IP20	i	4.92-275.59in 2.46in increments	KKFS IP65	i	5.00-275.67in 2.46in increments	(Specify length code OR total run length)																	

¹ External dimensions of IP65 version increase slightly due to silicone sleeve cover. IP65 variant only available with tail options. IP65 requires silicone mounting solutions, please see accessories.

² Not available for IP65

* Refer to **LED Grading Key** on **Specification sheet** page ** Refer to **Length Availability List** or enter total run length instead of length code

Code Example:

FS	-	s	-	113	-	30K	-	m	502	-	20	-	a	-	4	-	g
KKFS		HCRI	KKFS	3000K	502mm	IP20	50mm/1.97"	Double IP20 connector	DC 24V								

ACCESSORIES

Mounting Accessories

KKCP-07	Side clip
KKCP-08	IP65 Side clip
KKBK-14	IP65 Silicone bracket

* Refer to **Mounting Accessories** on **Accessories** pages

Connection Accessories

KKCN-01	2 PIN male & female 50mm/1.97" pair
KKCN-03	2 PIN male & female 300mm/11.81" pair
KKCN-06	2 PIN 300mm/11.81" extension lead

* Refer to **Connectors** on **Accessories** pages

PSU/Driver

0-10V/1010V/Dali/DMX

* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

LED ENGINE VARIANTS (LED STRIP TYPE)

Luminaire	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
KKFS	113	415	119	6.5	1.99	KKFS	125-7000mm/4.92-275.59in (IP20) 127-7002mm/5.00-275.67in (IP65)	62.5mm/2.46in

* Performance data: 3000K