

FIXTURE

Model	Finish	Cover	Grade*	LED	Colour (CCT)	Length Availability**	IP	Cable Length	Power Feed***	Input													
LiNi-S	LS	Silver Anodised	SA	Clear	B	s	352	1900K ¹	19K	m	97.3-2014mm 83.3mm increments	IP40	40	50mm/1.97"	a	Single tail	1	DC 24V	g				
					C			e	2100K					21K	i	3.83-79.29in 3.28in increments	300mm/11.81"			c	Double tail	2	
					G			k	2300K					23K			(Specify length code OR total run length)			1000mm/39.37"	d	Single IP20 connector	3
									2500K					25K						Double IP20 connector	4		
									2700K					27K									
									3000K					30K									
									3200K ¹					32K									
									3500K					35K									
									4000K					40K									
									5000K					50K									
									RED					RED						s-only			
									GREEN					GRN									
									BLUE					BLU									
									ORANGE					ORN									
									AMBER					AMB									

¹ 1900K is only available in k-line, 3200K is only available in s/e-line

* Refer to **LED Grading Key** on **Specification sheet** page ** Refer to **Length Availability List** or enter total run length instead of length code

Code Example:

LS	-	SA	-	C	-	s	-	352	-	35K	-	m	-	514	-	40	-	c	-	2	-	g
LiNi-S		Silver Anodised		Diffused				352		3500K		513.8mm		IP40		300mm/11.81"		Double tail		DC 24V		

ACCESSORIES
Mounting Accessories

KKCP-10 Concealed Clip

* Refer to **Mounting Accessories** on **Accessories** pages

Connection Accessories

KKCN-01 2 PIN male & female 50mm/1.97" pair

KKCN-03 2 PIN male & female 300mm/11.81" pair

KKCN-06 2 PIN 300mm/11.81" extension lead

* Refer to **Connectors** on **Accessories** pages

PSU/Driver

0-10V/1-10V/Dali/DMX

* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	Output	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Single CCT	Low	352	450	136	5.5	1.67	LiNi-S 352	97.3-2014mm/3.83-79.29in	83.3mm/3.28in
	Mid	504	1060	323	12.5	3.81	LiNi-S 504	114-2014mm/4.49-79.29in	100mm/3.94in
	High	508	1490	454	17.5	5.33	LiNi-S 508	85.4-2014mm/3.36-79.29in	71.4mm/2.81in
Warm Dim/Dynamic White	Tight Pitch	007	830	253	10.9	3.32	LiNi-S 007	97.4-2014mm/3.83-79.29in	41.7mm/1.64in
	Low	207	790	241	11	3.35	LiNi-S 207	97.3-2014mm/3.83-79.29in	83.3mm/3.28in
RGB	High	208	1310	399	15.6	4.75	LiNi-S 208	180.7-2014mm/7.11-79.29in	166.7mm/6.56in
		501			15.6	4.75	LiNi-S RGB	97.3-2014mm/3.83-79.29in	83.3mm/3.28in

* Performance data: s/e-line, Clear cover, 3000K