

LiNi-S Glow 209

Code Table



FIXTURE

Model	Finish	Cover	Grade*	LED	Colour (CCT)	Length Availability**	IP	Cable Length	Power Feed***	Input	
LiNi-S Glow	SG	Silver Anodised SA	Diffused C	¹ k	209	1900K 19K 2100K 21K 2300K 23K 2500K 25K 2700K 27K 3000K 30K 3500K 35K 4000K 40K 5000K 50K	m 94.4-2011mm 41.7mm increments i 3.72-79.17in 1.64in increments (Specify length code OR total run length)	IP40 40	50mm/1.97" a 300mm/11.81" c 1000mm/39.37" d	Single tail 1 Double tail 2 Single IP20 connector 3 Double IP20 connector 4	DC 24V g

¹ LEDmix requires two colour temperature choices

* Refer to **LED Grading Key** on **Specification sheet** page

** Refer to **Length Availability List** or enter total run length instead of length code

Code Example:

SG	-	SA	-	C	-	k	-	209	-	21K	-	35K	-	m	511	-	40	-	c	-	4	-	g
LiNi-S Glow		Silver Anodised		Diffused				209		2100K		3500K		511.4mm		IP40		300mm/11.81"		Double IP20 connector		DC 24V	

ACCESSORIES

Mounting Accessories

KKCP-02	Clip (1no.)
KKCP-52	Clip (500no.)

* Refer to **Mounting Accessories** on **Accessories** pages

Connection Accessories

KKCN-18	4 PIN LEDmix male & female 50mm/1.97" pair
KKCN-19	4 PIN LEDmix male & female 300mm/11.81" pair
KKCN-24	4 PIN LEDmix 300mm/11.81" extension lead

* Refer to **Connectors** on **Accessories** pages

PSU/Driver

0-10V/1-10V/Dali/DMX

* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Warm Dim/DynamicWhite	209	1030	314	25	7.62	LiNi-S Glow 209	94.4-2011mm/3.72-79.17in	41.7mm/1.64in

* Performance data: 2100K+5000K