


FIXTURE

Model	Finish	Cover	Grade*	LED	Colour (CCT)	Length Availability**	IP	Cable Length	Power Feed***	Input	
MiMi	MI	Silver Anodised SA	Clear B Diffused C	s e k	352	1900K ¹ 19K 2100K 21K 2500K 25K 2700K 27K 3000K 30K 3500K 35K 4000K 40K 5000K 50K RED RED  only GREEN GRN BLUE BLU ORANGE ORN AMBER AMB	m 103.3-2020mm 83.3mm increments i 4.07-79.53in 3.28in increments (Specify length code OR total run length)	IP54 54 IP67 ² 67	300mm/11.81" c	Single tail 1 Double tail 2 Single IP54 connector ³ 5 Double IP54 connector ³ 6 Single IP67 connector ⁴ 7 Double IP67 connector ⁴ 8	DC 24V g

¹ 1900K is only available in k-line

² Due to the clear, flush potted polyurethane top layer on IP67 MiMi a colour shift of +/-20K should be expected

³ Only available for IP54

⁴ Only available for IP67

* Refer to **LED Grading Key** on **Specification sheet** page

** Refer to **Length Availability List** or enter total run length instead of length code

Code Example:

MI	-	SA	-	C	-	s	-	352	-	35K	-	m	-	520	-	67	-	c	-	8	-	g
MiMi		Silver Anodised		Diffused				352		3500K		519.8mm		IP67		300mm/11.81"		Double IP67 connector		DC 24V		

ACCESSORIES

Mounting Accessories

KKCP-02	Clip (1no.)
KKCP-52	Clip (500no.)
KKCP-14	Lock Clip
KKBK-06	Fixed bracket
KKBK-05	Adjustable bracket

* Refer to **Mounting Accessories** on **Accessories** pages

Connection Accessories

CN54-2P-0300	IP54 2 PIN male & female 300mm/11.81" pair
CN54-2P-1000	IP54 2 PIN male & female 1000mm/39.37" pair
CN67-2P-0300	IP67 2 PIN male & female 300mm/11.81" pair
CN67-2P-1000	IP67 2 PIN male & female 1000mm/39.37" pair
CN67-2P-3000	IP67 2 PIN male & female 3000mm/118.11" pair

* Refer to **Connectors** on **Accessories** pages

Exterior Junction Boxes

KKJB-07	IP67 Slim J-Box
KKJB-07R	Potting Resin for IP67 Slim J-Box

* Refer to **Exterior Junction Boxes** on **Accessories** pages

PSU/Driver

0-10V/1-10V/Dali/DMX

* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	Output	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Single CCT	Low	352	340	103	5.5	1.67	MiMi 352	103.3-2020mm/4.07-79.53in	83.3mm/3.28in
	Mid	504	820	250	12.5	3.81	MiMi 504	120-2020mm/4.72-79.53in	100mm/3.94in
	High	508	1130	344	17.5	5.33	MiMi 508	91.4-2020mm/3.60-79.53in	71.4mm/2.81in
Warm Dim/Dynamic White	Tight Pitch	007	530	162	10.9	3.32	MiMi 007	103.4-2020mm/4.07-79.53in	41.7mm/1.64in
	Low	207	510	158	11	3.35	MiMi 207	103.3-2020mm/4.07-79.53in	83.3mm/3.28in
	High	208	1000	338	15.6	4.75	MiMi 208	186.7-2020mm/7.35-79.53in	166.7mm/6.56in
RGB		501			15.6	4.75	MiMi RGB	103.3-2020mm/4.07-79.53in	83.3mm/3.28in

* Performance data: s/e-line, Clear cover, 3000K