

### FIXTURE

Model	Finish	Cover	Grade*	LED	Colour (CCT)	Length Availability**	IP	Cable Length	Power Feed***	Input												
MiMi Glow	MG	Silver Anodised	SA	Diffused	C	k	k	008	1900K	19K	m	103.3-2020mm 41.7mm increments	IP54	54	300mm/11.81"	c	Single tail	1	DC 24V	g		
									2100K	21K							Double tail	2				
									2300K	23K							i	4.07-79.53in 1.64in increments			Single IP54 connector <sup>2</sup>	5
									2500K	25K											Double IP54 connector <sup>2</sup>	6
									2700K	27K											Single IP67 connector <sup>3</sup>	7
									3000K	30K											Double IP67 connector <sup>3</sup>	8
									3500K	35K											(Specify length code OR total run length)	
									4000K	40K												
									5000K	50K												

<sup>1</sup> Due to the clear, flush potted polyurethane top layer on IP67 MiMi a colour shift of +/-20K should be expected

<sup>2</sup> Only available for IP54 <sup>3</sup> Only available for IP67

\* Refer to **LED Grading Key** on **Specification sheet** page

\*\* Refer to **Length Availability List** or enter total run length instead of length code

### Code Example:

MG	-	SA	-	C	-	k	-	008	-	35K	-	m	-	520	-	54	-	c	-	6	-	g
MiMi Glow		Silver Anodised		Diffused				008		3500K		520.3mm		IP54		300mm/11.81"		Double IP54 connector		DC 24V		

### ACCESSORIES

#### Mounting Accessories

KKCP-14	Lock Clip
KKBK-24	Adjustable bracket

\* Refer to **Mounting Accessories** on **Accessories** pages

#### Connection Accessories

CN54-2P-0300	IP54 2 PIN male & female 300mm/11.81" pair
CN54-2P-1000	IP54 2 PIN male & female 1000mm/39.37" pair
CN67-2P-0300	IP67 2 PIN male & female 300mm/11.81" pair
CN67-2P-1000	IP67 2 PIN male & female 1000mm/39.37" pair
CN67-2P-3000	IP67 2 PIN male & female 3000mm/118.11" pair

\* Refer to **Connectors** on **Accessories** pages

#### Exterior Junction Boxes

KKJB-07	IP67 Slim J-Box
KKJB-07R	Potting Resin for IP67 Slim J-Box

\* Refer to **Exterior Junction Boxes** on **Accessories** pages

#### PSU/Driver

0-10V/1-10V/Dali/DMX

\* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

### LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Single CCT	008	583	177	20	6.09	MiMi Glow 008	103.3-2020mm/4.07-79.53in	41.7mm/1.64in

\* Performance data: 3000K