

### FIXTURE

Model	Finish	Cover/Lens*	Grade**	LED	Colour (CCT)	Length Availability***	IP	Cable Length	Power Feed****	Input			
MoMo MM	Silver Anodised SA	Clear	B	s	352	1900K <sup>1</sup>	m 103.3-2020mm 83.3mm increments	300mm/11.81" c	Single tail 1	DC 24V g			
			C	e	2100K	21K							
			P	k	2300K	23K							
		Clear+ KKLN-01					2500K	25K	i 4.07-79.53in 3.28in increments  (Specify length code OR total run length)		Double tail 2		
							2700K	27K					
							3000K	30K					
							3200K <sup>1</sup>	32K					
							3500K	35K					
							4000K	40K					
							5000K	50K					
							RED	RED					s-only
							GREEN	GRN					
							BLUE	BLU					
							ORANGE	ORN					
							AMBER	AMB					
								Single IP54 connector <sup>3</sup> 5					
								Double IP54 connector <sup>3</sup> 6					
								Single IP67 connector <sup>4</sup> 7					
								Double IP67 connector <sup>4</sup> 8					

<sup>1</sup> 1900K is only available in s/e-line, 3200K is only available in k-line

<sup>3</sup> Only available for IP54

<sup>2</sup> Due to the clear, flush potted polyurethane top layer on IP67 MoMo a colour shift of +/-20K should be expected

<sup>4</sup> Only available for IP67

\*\* Refer to **LED Grading Key** on **Specification sheet** page

\*\*\* Refer to **Length Availability List** or enter total run length instead of length code

### Code Example:

MM	-	SA	-	C	-	s	-	352	-	35K	-	m	-	520	-	67	-	c	-	8	-	g
MoMo		Silver Anodised		Diffused		s		352		3500K		519.8mm		IP67		300mm/11.81"		Double IP67 connector		DC 24V		

### ACCESSORIES

#### Mounting Accessories

KKCP-03	Clip (1no.)
KKCP-53	Clip (500no.)
KKCP-09	Lock Clip
KKBK-07	Fixing plate
KKBK-21	Adjustable bracket

\* Refer to **Mounting Accessories** on **Accessories** pages

#### Connection Accessories

CN54-2P-0300	IP54 2 PIN male & female 300mm/11.81" pair
CN54-2P-1000	IP54 2 PIN male & female 1000mm/39.37" pair
CN67-2P-0300	IP67 2 PIN male & female 300mm/11.81" pair
CN67-2P-1000	IP67 2 PIN male & female 1000mm/39.37" pair
CN67-2P-3000	IP67 2 PIN male & female 3000mm/118.11" pair

\* Refer to **Connectors** on **Accessories** pages

#### Exterior Junction Boxes

KKJB-07	IP67 Slim J-Box
KKJB-07R	Potting Resin for IP67 Slim J-Box

\* Refer to **Exterior Junction Boxes** on **Accessories** pages

#### PSU/Driver

0-10V/1-10V/Dali/DMX

\* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

### LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	Output	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Single CCT	Low	352	420	127	5.5	1.67	MoMo 352	103.3-2020mm/4.07-79.53in	83.3mm/3.28in
	Mid	504	990	302	12.5	3.81	MoMo 504	120-2020mm/4.72-79.53in	100mm/3.94in
	High	508	1370	418	17.5	5.33	MoMo 508	91.4-2020mm/3.60-79.53in	71.4mm/2.81in
Warm Dim/Dynamic White	High	512	2370	720	30.2	9.2	MoMo 512	91.4-2020mm/3.60-79.53in	71.4mm/2.81in
	Low	207	720	219	11	3.35	MoMo 207	103.3-2020mm/4.07-79.53in	83.3mm/3.28in
	High	208	1210	409	15.6	4.75	MoMo 208	186.7-2020mm/7.35-79.53in	166.7mm/6.56in
RGB		501			15.6	4.75	MoMo RGB	103.3-2020mm/4.07-79.53in	83.3mm/3.28in

\* Performance data: s/e-line, Clear cover, 3000K