

### FIXTURE

Model	Finish	Cover	Grade*	LED	Colour (CCT) <sup>2</sup>	Length Availability**	IP	Cable Length	Power Feed***	Input	
MoMo-BLOC BL	Silver Anodised SA	Frosted Glass M	s	352	2300K (2100K PCB) <sup>4</sup>	m 524/1024mm <sup>3</sup> i 203.63/40.31in <sup>3</sup>	IP67 67	300mm/11.81" c	Single tail 1 Double tail 2 Single IP67 connector 7 Double IP67 connector 8	DC 24V g	
											Hard Anodised <sup>1</sup> HA
			k		2500K (2300K PCB) <sup>4</sup>						25K
					3000K (2500K PCB)						30K
					3400K (2700K PCB)						34K
					4000K (3000K PCB)						40K
					RED						RED s-only
					GREEN						GRN
					BLUE						BLU
					ORANGE						ORN
		AMBER	AMB								

<sup>1</sup> Hard anodised finish reduces light output by an average of 30%    <sup>2</sup> Actual colour temperature after colour shift caused by silicone potting

<sup>3</sup> 2 lengths available on all PCB types

<sup>4</sup> k-line: 2300K (1900K PCB)/ 2500K (2100K PCB)

\* Refer to **LED Grading Key** on **Specification sheet** page

\*\* Refer to **Length Availability List** or enter total run length instead of length code

### Code Example:

BL	-	SA	-	M	-	s	-	352	-	40K	-	m	524	-	67	-	c	-	8	-	g
MoMo-BLOC		Silver Anodised		Frosted Glass		s		352		4000K (3000K PCB)		m	524mm		IP67		300mm/11.81"		Double IP67 connector		DC 24V

### ACCESSORIES

#### Mounting Accessories

KKBG-01	Ground box 01
KKBG-02	Ground box 02
KKBG-03	Ground box 03

\* Refer to **Mounting Accessories** on **Accessories** pages

#### Connection Accessories

CN67-2P-0300	2 PIN male & female 300mm/11.81" pair
CN67-2P-1000	2 PIN male & female 1000mm/39.37" pair
CN67-2P-3000	2 PIN male & female 3000mm/118.11" pair

\* Refer to **Connectors** on **Accessories** pages

#### Exterior Junction Boxes

KKJB-07	IP67 Slim J-Box
KKJB-07R	Potting Resin for IP67 Slim J-Box

\* Refer to **Exterior Junction Boxes** on **Accessories** pages

#### PSU/Driver

0-10V/1-10V/Dali/DMX

\* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

### LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	Output	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length
Single CCT	Low	352	100	31	5.5	1.67	MoMo-BLOC 352	524/1024mm 20.63/40.31in
	Mid	504	230	70	12.5	3.81	MoMo-BLOC 504	524/1024mm 20.63/40.31in
	High	508	320	98	17.5	5.33	MoMo-BLOC 508	524/1024mm 20.63/40.31in
	Tight Pitch	007	182	56	10.9	3.32	MoMo-BLOC 007	524/1024mm 20.63/40.31in
RGB		501			15.6	4.75	MoMo-BLOC RGB	524/1024mm 20.63/40.31in

\* Performance data: s/e-line, 3000K