





FIXTURE

Model	Finish	Cover/Lens*	Grade**	LED	Colour (CCT)	Length Availability***	IP	Cable Length	Power Feed****	Input
MoMo-L MO	Silver Anodised SA	Clear	B  s	352	1900K ¹ 19K	m 103.3-2020mm 83.3mm increments	IP54 54	300mm/11.81" c	Single tail 1	DC 24V g
		Diffused	C  e		2100K 21K					
		Clear+KKLN-01	P  k		2300K 23K	(Specify length code OR total run length)			Single IP54 connector ³ 5	
		Clear+ Micro Louvre	K		2500K 25K					
					2700K 27K	Single IP67 connector ⁴ 7				
		Clear+ KKLN-01+ Micro Louvr	U		3000K 30K		Double IP67 connector ⁴ 8			
		Diffused+ Micro Louvre	?		3200K ¹ 32K					
					3500K 35K					
					4000K 40K					
					5000K 50K					
					RED RED  only					
					GREEN GRN					
					BLUE BLU					
					ORANGE ORN					
		AMBER AMB								

¹ 1900K is only available in s/e-line, 3200K is only available in k-line

³ Only available for IP54

² Due to the clear, flush potted polyurethane top layer on IP67 MoMo a colour shift of +/-20K should be expected

⁴ Only available for IP67

** Refer to **LED Grading Key** on **Specification sheet** page

*** Refer to **Length Availability List** or enter total run length instead of length code

Code Example:

MO	-	SA	-	C	-	s	-	352	-	35K	-	m	-	520	-	67	-	c	-	8	-	g
MoMo-L		Silver Anodised		Diffused				352		3500K		519.8mm		IP67		300mm/11.81"		Double IP67 connector		DC 24V		

ACCESSORIES

Mounting Accessories

KKCP-03	Clip (1no.)
KKCP-53	Clip (500no.)
KKCP-17	Lock Clip
KKBK-07	Fixing plate
KKBK-21	Adjustable bracket

* Refer to **Mounting Accessories** on **Accessories** pages

Connection Accessories

CN54-2P-0300	IP54 2 PIN male & female 300mm/11.81" pair
CN54-2P-1000	IP54 2 PIN male & female 1000mm/39.37" pair
CN67-2P-0300	IP67 2 PIN male & female 300mm/11.81" pair
CN67-2P-1000	IP67 2 PIN male & female 1000mm/39.37" pair
CN67-2P-3000	IP67 2 PIN male & female 3000mm/118.11" pair

* Refer to **Connectors** on **Accessories** pages

Exterior Junction Boxes

KKJB-07	IP67 Slim J-Box
KKJB-07R	Potting Resin for IP67 Slim J-Box

* Refer to **Exterior Junction Boxes** on **Accessories** pages

PSU/Driver

0-10V/1-10V/Dali/DMX

* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	Output	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Single CCT	Low	352	320	100	5.5	1.67	MoMo-L 352	103.3-2020mm/4.07-79.53in	83.3mm/3.28in
	Mid	504	760	232	12.5	3.81	MoMo-L 504	120-2020mm/4.72-79.53in	100mm/3.94in
	High	508	1040	317	17.5	5.33	MoMo-L 508	91.4-2020mm/3.60-79.53in	71.4mm/2.81in
Warm Dim/Dynamic White	High	512	1800	548	30.2	9.2	MoMo-L 512	91.4-2020mm/3.60-79.53in	71.4mm/2.81in
	Low	207	570	171	11	3.35	MoMo-L 207	103.3-2020mm/4.07-79.53in	83.3mm/3.28in
	High	208	920	311	15.6	4.75	MoMo-L 208	186.7-2020mm/7.35-79.53in	166.7mm/6.56in
RGB		501			15.6	4.75	MoMo-L RGB	103.3-2020mm/4.07-79.53in	83.3mm/3.28in

* Performance data: s/e-line, Clear cover, 3000K