

FIXTURE

Model	Finish		Cover		Grade*		LED	Colour (CCT)		IP		Cable Length	Power Feed**		Input			
TAYO Micro Indoor	TR	Silver Anodised SA	Diffused C		s	s	106	2700K 27K	3000K 30K	3500K 35K	5000K 50K	RED RED	GREEN GRN	BLUE BLU	IP54 54	1000mm/39.37" d	Single tail 1	DC 12V f

* Refer to **LED Grading Key** on **Specification sheet** page

Code Example:

TR	-	SA	-	C	-	s	-	106	-	30K	-	54	-	d	-	1	-	f
TAYO Micro Indoor		Silver Anodised		Diffused		s		TAYO Micro		3000K		IP54		1000mm/39.37"		Single tail		DC 12V

ACCESSORIES

Exterior Junction Boxes

KKJB-07	IP67 Slim J-Box
KKJB-07R	Potting Resin for IP67 Slim J-Box

* Refer to **Exterior Junction Boxes** on **Accessories** pages

PSU/Driver

0-10V/1-10V/Dali/DMX

* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

LED ENGINE VARIANTS (LED STRIP TYPE)

Luminaire	LED	Lumen/m (ft)	W	Spec Doc	Dimension
TAYO Spot	107	49/module	1.62	TAYO Spot	H63/Ø56mm H2.48/Ø2.20in
TAYO Ceiling	107	49/module	1.62	TAYO Ceiling	H63/Ø66mm H2.48/Ø2.60in
TAYO Micro Outdoor	106	2.19/module	0.14	TAYO Micro (Outdoor)	H63.9/Ø30mm H252/Ø1.18in
TAYO Micro Indoor	106	3.25/module	0.14	TAYO Micro (Indoor)	H57.7/Ø30mm H2.27/Ø1.18in

* Performance data: 3000K