

### FIXTURE

Model	Finish	Cover/Lens*	Grade**	LED	Colour (CCT)	Length Availability***	IP	Cable Length	Power Feed****	Input													
TiMi-M	IM	Silver Anodised SA	No cover <sup>1</sup>	X	352	1900K <sup>3</sup>	m	IP20	20	50mm (1.97in)	Single tail	1	DC 24V	g									
						19K									97.3-2014mm <sup>1</sup>	a							
						2100K									90.3-2007mm <sup>2</sup>		c						
						21K									83.3mm increments								
						2500K									i 3.83-79.29in <sup>1</sup>			Double tail	2				
						25K									3.56-79.01in <sup>2</sup>								
						2700K									3.28in increments					Single IP20 connector	3		
						27K									(Specify length code OR total run length)								
						3000K									30K							Double IP20 connector	4
						3500K									35K								
						4000K									40K								
						5000K									50K								
						RED									RED								
GREEN	GRN																						
BLUE	BLU																						
ORANGE	ORN																						
AMBER	AMB																						

<sup>1</sup> Double clamp TiMi length

<sup>2</sup> Single clamp TiMi length

<sup>3</sup> 1900K is only available in k-line

<sup>4</sup> Operating temperatures vary for TiMi-M with cover and TiMi-M without cover; please check with a KKDC engineer if operating temperature is limiting product application

\*\* Refer to **LED Grading Key** on **Specification sheet** page

\*\*\* Refer to **Length Availability List** or enter total run length instead of length code

### Code Example:

IM	-	SA	-	D	-	s	-	352	-	35K	-	m	-	514	-	20	-	a	-	4	-	g
TiMi-M		Silver Anodised		Semi-diffused				352		3500K				513.8mm		IP20		50mm (1.97in)		Double IP20 connector		DC 24V

### ACCESSORIES

#### Mounting Accessories

**KKBK-20** Steel plate

\* Refer to **Mounting accessories** on **Accessories** pages

#### Connection Accessories

**KKCN-01** 2 PIN male & female 50mm (1.97in) pair

**KKCN-03** 2 PIN male & female 300mm (11.81in) pair

**KKCN-06** 2 PIN 300mm (11.81in) extension lead

\* Refer to **Connectors** on **Accessories** pages

#### PSU/Driver

0-10V/1-10V/Dali/DMX

\* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

### LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	Output	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Single CCT	Low	352	510	155	5.5	1.67	TiMi-M 352	97.3-2014mm (3.83-79.29in)	83.3mm (3.28in)
	Mid	504	1240	378	12.5	3.81	TiMi-M 504	114-2014mm (4.49-79.29in)	100mm (3.94in)
	High	508	1720	524	17.5	5.33	TiMi-M 508	85.4-2014mm (3.36-79.29in)	71.4mm (2.81in)
Warm Dim/Dynamic White	Tight Pitch	007	950	290	10.9	3.32	TiMi-M 007	55.7-2014mm (2.19-79.29in)	41.7mm (1.64in)
	Low	207	900	274	11	3.35	TiMi-M 207	97.3-2014mm (3.83-79.29in)	83.3mm (3.28in)
	High	208	1510	460	15.6	4.75	TiMi-M 208	180.7-2014mm (7.11-79.29in)	166.7mm (6.56in)
RGB		501			15.6	4.75	TiMi-M RGB	97.3-2014mm (3.83-79.29in)	83.3mm (3.28in)

\* Performance data: s/e-line, No cover, 3000K