


PRODUCT SPECIFICATION

Dimension	H8/W7.8/L23mm (H0.32/W0.31/L0.91in) (2 pole, male + female connected) H8/W12.8/L17mm (H0.32/W0.5/L0.67in) (4 pole, male + female connected) H8/W15.3/L17mm (H0.32/W0.6/L0.67in) (5 pole, male + female connected)
Operating Temp	T _a = -25 to 85°C (-13 to 185°F)
IP Rating	IP20
Finish	White
Shell Materials	Nylon PA66, fire resistance (UL94): V-0
Contact Materials	Brass with phosphor bronze plating
Rated Current	AC/DC 3A
Rated Voltage	AC/DC 250V
Test Voltage	1000V (AC, V/1min)
Contact Resistance	30mΩ
Insulation Resistance	1000MΩ
Applicable Wire	22-28 AWG




Female



	A	B	C	D
2 pole	7.2mm (0.28in)	5.79mm (0.23in)	2.5mm (0.1in)	3.0mm (0.12in)
4 pole	12.2mm (0.48in)	10.79mm (0.43in)	7.5mm (0.3in)	5.0mm (0.2in)
5 pole	14.7mm (0.58in)	13.29mm (0.52in)	10.0mm (0.39in)	5.0mm (0.2in)

Male



	A	B	C
2 pole	7.8mm (0.31in)	5.8mm (0.23in)	2.5mm (0.1in)
4 pole	12.8mm (0.5in)	10.8mm (0.43in)	7.5mm (0.3in)
5 pole	15.3mm (0.6in)	13.3mm (0.52in)	10.0mm (0.39in)