

IP67 Slim J-Box (KKJB-07)

Specification sheet

KKDÖ

IP67 CE

ORDER CODE KKJB-07 – (Please check KKDC Junction Box guide).

PRODUCT SPECIFICATION
Dimension H11.6/W15/L62mm (H0.4/W0.6/L2.4in)

Operating Temp $T_a = -25$ to 70°C (-13 to 158°F)

Storage Temp $T_a = -25$ to 70°C (-13 to 158°F)

IP Rating IP67

Finish Matt Black

Components Case, 2x terminal, 4x bush pairs

Materials Case – nylon
Terminals – bronze
Bushes – PVC

Cable & Connectors 2 core terminals

Potting Fast set epoxy resin – **KKJB-07R**
Bushes 4 pairs of bushes supplied with each IP67 Slim J-Box:

- | | |
|--|---|
| A type – $\varnothing 4.3\text{mm}$ (0.17in) sheathed cable | Groove Light IP67 (2 core only)/KKSL/KURV-Y LEDmix/KURV-Y RGB/MiMi/MiMi Glow/MoMo/MoMo-BLOC/MoMo-L/POKI |
| B type – $\varnothing 6.3\text{mm}$ (0.25in) sheathed cable | MoMo-F/MoMo Sauna/SEN/SEN CV/SEN-F/SEN-F CV/SEN Louvre/SEN Louvre CV/SUMO/TAYO Ceiling (2 core only)/TAYO Micro (outdoor)/TAYO Spot |
| C type – ellipse sheathed cable | Luna (2 core only) |
| D type – $\varnothing 3.5\text{mm}$ (0.14in) sheathed cable | KURV-Y (2 core only) |

